



Halkalı Merkez Mah. Dereboyu Cad. Antplato. No:4 İç Kapı No:112 Küçükçekmece / İstanbul

www.final-ticaret.com info@final-ticaret.com

NAME: P-FI-090 Homopolymer

Product Description:

"Polynar P-FI-090" is a polypropylene homopolymer for injection moulding. "Polynar P-FI-090" its good flow properties, this grade offers easy processing. Articles produced from "Polynar P-FI-090" exhibit high stiffness. "Polynar P-FI-090" is widely used for injection moulding consumer goods such as food containers, house wares, toys & garden furniture. Other major applications are components for appliances & parts for the automotive industry. "Polynar P-FI-090" is suitable for food contact.

Typical Applications:

Homopolymer, good flow properties, easy processing, high stiffness, injection moulding consumer goods such as food containers ,house, wares, toys , garden furniture & are components for appliances & parts for the automotive industry.

Typical data: (Table)

Test/Composition	Value	Unit	Method
Melt flow rate(230°C /2.16 kg)	10	dg/min	ASTMD1238
Density	0.9	g/cm3	ASTMD 1505
Flexural Modulus	1550	MPa	ASTMD790
Tensile Strength at Yield	35	MPa	ASTM D 638
Tensile Elongation at Yield	12	%	ASTM D638
Izod Impact Strength (notched) at 23 °C	37	J/m	ASTM D256
Vicat softening point (ION)	154	°C	ASTMD 1525
H.D.T (0.46 MPa)	95	°C	ASTM D 648

Maine Application: Injection molding Product Type: Homo polymer